


- TERRACOTTA
- QUARRY TILES
- PORCELAIN TILES
- STONE AND AGGLOMERATES
- CONCRETE



WHAT IT'S FOR

- Protects terracotta, quarry tiles, porcelain tiles, cement and natural stone from water and damp.
- Penetrates into materials strengthening the surface.
- Removes any water seepage problem.
- Prevents water seepage, and formation of mould and efflorescence and consequently any serious structural issues.
- Protects grout joints.
- Penetrates into small cracks (from 0.5 µm to 1 mm) making them water repellent.

Packaging

1-litre cans in boxes of 12.
5-litre cans in boxes of 4.

ADVANTAGES

- It does not form surface film and allows treated materials to breathe.
- Easy to use because it is ready to apply.
- Does not yellow with ageing or due to any environmental condition.
- Provides high coverage.

HOW IT WORKS



Salvaterrazza removes any water seepage problems which form mould, efflorescences and further structure issues with frost.



The product penetrates into fissures and bonds chemically with the material increasing its solidity.



Salvaterrazza prevents water penetration but lets the material breathe without creating any superficial film.

HOW TO USE IT

No dilution required: ready to use.

Application:

Wash the floor thoroughly with a de-greasing detergent **FILAPS87** or **DETERDEK** according to need. When the floor is dry, apply **SALVATERRAZZA** evenly over the entire surface, using a paintbrush or other applicator, taking care to impregnate joints and cracks thoroughly. **Work into the surface with a cloth within 5 minutes so as to dry it and remove any excess product thoroughly.** The paving can be walked on 24 hours after the final coat.

Caution:

On particularly absorbent materials such as sandstone, limestone, terracotta and concrete, apply a second coat 24 hours after the first, following the same procedure. The product may brighten the material, so we recommend testing its reaction beforehand on a small area. Do not apply the product externally if rain is forecast.

COVERAGE

With one litre:

Terracotta, Stone	10/15 m²
Porcelain tiles, Quarry tiles	30 m²

Coverage shown is for guidance purposes only and refers to single coats

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

TEMPERATURES

Storage temperature: from 0° to 30°C.
The product should be applied to materials with temperature between 5° and 30° C.

COMPOSITION

- A mixture of siloxane compounds dispersed in de-aromatised hydrocarbon solvent.
- Pursuant to It.Leg.Dec. No.161/06 class: Fixative primers (consolidator)
EU limit value for this product (Cat: 1/h): 750 g/l (2010)
This product contains no more than 624.87 g/l

LABELLING

Warning: Danger

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.



If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations. Contains: NAPHTA (PETROL.) HYDROTREATED HEAVY

TECHNICAL FEATURES

Appearance: liquid
Colour: colourless
Odour: slight hydrocarbon solvent smell
Density: 0.777 kg/l
Flash point: 40 °C

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.